

C023 UNDERWATER CUT-OFF SAW

STANLEY



The **C023** Cut-Off Saw is a hydraulic powered saw for dimensional cutting of metal, concrete, rock, masonry and coral. It has a high torque gear motor and 10" blade capacity for abrasive and diamond wheels with a 1" arbor. The **C023** is designed for underwater operation and is painted hi-visibility yellow.

FEATURES

- Integral Stanley Hyrevz gear motor produces high torque
- Direct drive motor
- Stainless Steel spool and fasteners
- Adjustable shoe for precise cuts
- Interlocking safety trigger
- Cast aluminum handle and guard for durability
- Counter-clockwise rotation
- Wide flow range

SPECIFICATIONS

Capacity	10" / 25.4 cm wheel
Performance	3275 rpm @ 15 gpm
Arbor	1" / 2½ cm
Circuit Type	Open Center
Flow Range	10-15 gpm / 38-57 lpm
Optimum Flow	15 gpm / 57 lpm
Working Pressure	1500-2000 psi / 105-140 bar
Full Relief Setting	2250 psi / 155 bar
Weight	23 lbs / 10.4 kg
Length	19½" / 49½ cm
Width	11" / 28 cm
Hydraulic Ports	-8 SAE O-ring
Connection Size and Type	½" Male Pipe Hose End
Couplers	No (See Accessories)
Hose Whips	Yes



C023 UNDERWATER CUT-OFF SAW

STANLEY

ORDERING INFORMATION

PART NUMBER

C023341 Cut-Off Saw, Underwater, 10" capacity with 1" arbor, less couplers

ACCESSORIES

03971 Flush-Face Coupling Set, 3/8" NPT

03974 Flush-Face Coupling Set, 1/2" NPT

06830 Hose Whip 18" long, -8 SAE x 1/2" NPT

03694 10" / 25.4 cm diameter, 1" arbor, diamond blade for concrete

04116 10" / 25.4 cm diameter, 1" arbor, abrasive blade for concrete

04117 10" / 25.4 cm diameter, 1" arbor, abrasive blade for aluminum and metal

31848 Dual Hose, 50' x 1/2", with couplers

31972 Dual Hose, 25' x 1/2", with couplers


58633 Twinned Hose, 25' x 1/2", with couplers

58634 Twinned Hose, 50' x 1/2", with couplers

When hydraulic hose exceeds 100' (30.4 m) in length, increase I.D. of both pressure and return hose. For more information, consult Stanley Hydraulic Tools.

IMPORTANT

To fill out a Product Warranty Recording form and for information on your warranty visit stanleyhydraulic.com and select the Warranty tab.



Note: The warranty recording form must be submitted to validate the warranty.

All Stanley Hydraulic Tools, parts, accessories and allied equipment are subject to design improvements, specifications and price changes at any time without notice and with no obligation to units already sold. Weights, dimensions and operating specifications listed herein are subject to change without notice. Where specifications are critical to your applications, please consult Stanley Hydraulic Tools.