



CCTV Inspection Systems and Underwater Lighting



Doc-MVF5-V-2022

MVF-5

UNDERWATER LED FLOODLIGHT

MARINE VISION S.L.

Polígono Industrial La Vega, nave 19; 29650 Mijas-Costa (Málaga) ESPAÑA
Tel: (+34) 952 473 230 | Fax: (+34) 952 585 545 | email: comercial@marinevision.es | www.marinevision.es

DESCRIPTION

The MVF-5 floodlight is specially made for video recording and also as general illumination for the diver.

Its equipped with a 1450lm LedCob with a suitable color temperature for video recording.

The floodlight is equipped with a reflector that enhances the spatial reflection and gives an even light pattern.

The floodlight is normally used together with the MVR-5 underwater CCTV system, but special versions are available with 12-30V and PWM intensity control.



Referencia	Descripción
MV-MVF-5	floodlight MVF-5

Specifications

Power requirements:	1A@10-14VDC (thru driver or directly with PWM regulation).
Secondary voltage:	n/a.
Relative Flux:	1450lm@1Amp, T=25°
Color temperature:	6500 K.
Angle of light:	120°
Material housing:	Anodized clear coated aluminium.
Other materials:	HD Delrin, Polycarbonate, NPDM, Brass.
Max depth rating:	150 msw.
Connector:	SubConn®.
Length:	120 mm.
External width (nut):	56 mm.
Diam housing:	42 mm.
Aprox weight:	aprox. 300 g.

Marine Vision reserves the right to make changes to specifications without notice.